



DIAMOND TUBE TOP BEAM

Top sidewall beam is inclined to eliminate material spillage.







TAPERED BODY

The inside of dump body width is tapered outward from the front to rear for better clean out.



All our Lanau dump bodies are fitted with rear post tail lights and at least (5) side marker lights for increased visibility.



VARIETY OF MODELS & LENGTHS While our most

commonly stocked box is 15 feet long, we can custom order a box to fit your needs.



TAILGATE

Staylock tailgate

latching system

stays closed when

guarantees the tailgate

SYSTEM

loaded.

A rubber cushion is mounted between the front sill and truck frame to minimize body rattle.

SPECIFICATIONS

| BOX SIZE | Various sizes available; dependent on customers' needs |
|---------------------------|---|
| FLOOR | Hardox 3/6" hi-tensile steel 205,000 psi steel |
| REAR INSIDE HEIGHT | 88 5/8" |
| SIDE HEIGHT | 24", 30", 26", 42", 28", 54", & 60" |
| SIDES | Hardox 1/8" hi tensile 205,000 psi steel 4" x 3" Diamond tube top beam (3) Sideboard support brackets per side |
| FRONT | Hardox 1/8" hi tensile 205,000 psi steel |
| TAILGATE | Hardox 3/16" hi tensile 205,000 psi steel (3) Horizontal stiffeners c/w spreader chain adjustment slots |
| TAILGATE TRIP | Air controlled 4" doubling acting pneumatic cylinder |
| TAILGATE HEIGHT | 36", 48", 54", 60" & 72" |
| CAB SHIELD | 12", 18", 24", 30", 36" & 42" |
| HOIST | Outside or inside mount hoist; dependent on customers' needs |
| RIDE CUSHION | Rubber cushion mounted on front box sill underside |
| LIGHTING SYSTEM | Sealed integrated wiring harness system (2) Oval LED tail/turn & (1) backup in rear corner posts (5) 2" LED clearance per side & (3) 2" LED ID in center at rear |
| WET KIT | Direct mount air shift PTO & pump Air operated auto PTO kick out & pump feathering valve Multi-function floor mount control console (3) Line system - supply, suction, & return |
| HYDRAULIC SELECTOR | Cross 3 port air controlled |
| HYDRAULIC TANKS | Aluminum frame mount; tank size dependent on box size |
| HITCH ASSEMBLY (optional) | Hi tensile steel frame insert style rear apron Premier 370 pintle hook, air assisted slack |

MUD FLAPS

(2) Rubber mudflaps installed in front of 2nd axle & behind 3rd axle
(2) Anti-sail brackets installed on front mud flaps

SIDEBOARDS

Spruce 2" x 12" smooth

FINISH

Box sandblasted & baked powder coated paint (1) color
Sideboards painted black with acrylic enamel

LOAD COVER

Electric drive mesh flip tarp c/w polished

OPTIONS

- Quick-Slide UHMW box liner
- Air Weigh scale system
- Dump body vibrator
- Sealed tailgate and hazard safety locks
- . High lift tailgate & hinge point
- Shovel mount

Product improvement is an ongoing process. The manufacturer reserves the right to change any specifications or components on any or all products without prior notice and is under no obligation to undertake modifications to units manufactured to prior changes in specifications.



control

TOLL FREE: 1-877-962-9110 www.hayworthequipment.com