

# GINCOR SUPER B FLAT DECK

#### **DECKING**

1 5/16" fir ship lap & linseed oil treated.

#### **CENTER BRIDGE**

Aluminum walking deck with left & right side steps for easy access.

#### **LOAD SECUREMENT**

(39) 3-bar winches and J-hooks line the outside frame of the lead & pup and have all tested to meet current load securement regulations.

#### LIGHTS

High visibility 4" LED lamps on rear Stop/ Turn/Tail/Strobe & ID lights so the trailer is seen in all weather conditions.

### **TWO-SPEED LANDING GEAR**

This trailer is equipped with Holland Mark V two-speed landing gear, which has a static load rating of 120,000 lbs.

#### **FRAME**

100,000 psi high tensile steel is used for the flange and the webb, making this a strong trailer with a long service life.

#### **FULL MUDFLAP PACKAGE**

This trailer comes standard equipped with 3 mudflaps ahead of the landing gear on the lead & pup, with 2 mudflaps ahead and behind axle groups.

#### **ALUMINUM TOOLBOXES**

Two 24"x30"x60" toolboxes on lead trailer and two on the pup. The toolboxes utilize a no-fuss locking system that won't freeze up in the winter.

#### View our full trailer product line

Photos, specs, and more can be found on our website hayworthequipment.com



#### The right truck and trailer steering your business in the right direction.

At Hayworth Equipment Sales, we believe that our success depends on yours. We are committed to providing you with experienced advice and personalized services that make your equipment run smoother as well as your business. A trailer is not just a trailer, see the difference with Hayworth.



1-877-962-9110





**26180 - 114 AVENUE ACHESON, AB T7X 6R1** 



## **SPECIFICATIONS**

2024 MODEL	Lead: 323FDL-S & Pup: 282FDP-S
LENGTH	Overall combined length: 63'6" Lead: 32'0" & Pup: 28'0"
WIDTH	8'6"
DECK HEIGHT	Lead: 60"at front Pup: 51" at rear
COUPLER	2" Holland king pin
KING PIN PLATE	5/16" @ 49" height on lead trailer
KING PIN SETTING	Lead: 30", Pup: 18"
SWING CLEARANCE	88"
MAIN BEAMS	Flange: 3/8" x 5" top & bottom 100kpsi Webb: 3/16"80kpsi
CROSSMEMBERS	High tensile 4" Jr. I-beam @ 16" o.c.
SIDE RAIL	4"x3" high tensile rectangular tube $1/4"$ bar near top to protect safety tape from load strap damage
FIFTH WHEEL	Holland fixed mount on bridge of lead
STAKE POCKETS	Pocket in side rail set to flush@ 24" o.c. (4) Pockets in front & rear of lead and pup set flush
LOAD SECUREMENT	(39) 3-Bar winches & J hooks opposite onside rails, rope hooks at 24" o.c. on sides & (4) across front & rear
STORAGE	(4) Iconic 24" x 30" x 60" aluminum tool boxes (2) on lead and (2) on pup
DECKING	1 5/16" ship lap fir throughout
LANDING GEAR	Holland Mark V two speed crank down 120,000lb capacity
REAR BUMPER	Pup: 4" x 4" tube style DOT approved
FENDERS	Poly 180° tub style fenders over lead axles
AXLES	(5) 25,000 lb.@ 77" track

AXLE SPREAD	Lead: 60" & Pup: 49"
SUSPENSION	(5) Dexter Smart-AXL 25,000lb airride Tuff-Lift load sensing on 1st, 2nd & 4th axles
BRAKE CHAMBERS	Bendix 30/30 parking brakes
AIR BRAKE SYSTEM	Wabco 4S/2M ABS on lead
SLACK ADJUSTERS	Meritor automatic self adjusting
CAMSHAFTS	28 spline c/w enclosed tubes
HUB & DRUMS	10 stud hub piloted, long stud & outboard cast drums
TIRES	(20) Aeolus HN808 - 11R-22.5 radial
WHEELS	(20) Alcoa aluminum 10 stud pilot mount 8.25 x 22.5 - polished
ELECTRICAL System	Grote Ultra Blue integrated wiring system Seven pin female plug @ front of each trailer (2) pair of aluminum pullout lights on lead & pup trailer
FINISHING	Sandblasted, epoxy primer & Genesis polyurethane paint
SAFETY TAPE	Applied as per CMVSS regulations
WARRANTY	1 <sup>st</sup> year - 100% parts & labour 2 <sup>nd</sup> year - 50% parts & labour 3 <sup>rd</sup> to 5 <sup>th</sup> year - 50% parts only

#### **PRICE**

\*Quote valid for 14 days, All taxes extra.

\$119,900\*

#### Monthly payments as low as \$2,190.00 + Tax

Thank you for your interest in our product and we look forward to providing you with the best value transportation equipment available.

Sincerely,

Hayworth Equipment Sales Inc.

Sales Representative









